



# FOUNTAIN INDUSTRIES



## Parts Washers





## SOLVENT PARTS WASHER

### CleanMaster 400

Low-profile portable solvent brake washer. Equipped with handle, flow-through brush, and locking casters. This unit is designed for portability and to effectively clean brake components without removing parts from the vehicle. For use with petroleum based solvents with a flash point over 104°F. Not to be u



### Features

- Durable, baked on powder coated epoxy finish .
- Split-lid with fusible links 165°F
- Removable work tray
- Flow-through brush for efficient cleaning
- Easy-roll swivel casters (2 locking)

### Specifications

- Overall dimensions: 36" L x 26" W x 12" H
- Inside dimensions: 32" L x 22" W x 10" H
- Shipping dimensions: 37 ½" L x 27 ½" W x 13" H
- Weight: 50 lbs.
- Fluid capacity: 17 ½"
- Maximum fluid depth: 5¾"
- Minimum fluid depth: 2¾"
- Voltage: 115VAC/60HZ/1PH/1 Amp
- Pump: Fractional



## SOLVENT PARTS WASHER

### CleanMaster 60

Table top solvent parts washer. Equipped with flow-through brush which works great for cleaning small parts. This unit could be used as a table top parts washer or use with the optional rolling cart for a more portable solution. For use with petroleum based solvents with a flash point over 104°F. Not to be used with chlorinated solvents.

### Features

- » Durable, baked on powder coated epoxy finish
- » Fire-protective lid closure up to 165°F
- » Flex hose with brush

### Specifications

- » Overall dimensions: 28½" L x 14" W x 22" H
- » Inside dimensions: 25" L x 14" W x 9" H
- » Shipping dimensions: 29" L x 16" W x 11" H
- » Weight: 52 lbs.
- » Fluid capacity: 5 gallons
- » Maximum fluid depth: 3¼"
- » Minimum fluid depth: 2½"
- » Voltage: 115VAC/60HZ/1PH/1 Amp
- » Pump: Fractional

### Accessories

- » 55567 - Rolling Cart (optional)
- Shipping dimensions cart: 5" H x 19" W x 31" L
- Shipping weight: 53 lbs.
- Height down with cart: 12¾"
- Height up with cart: 36¾"





## SOLVENT PARTS WASHER

### CleanMaster 130

Economy drum mounted solvent parts washer. Built-to-last for years of reliable service. Equipped with “stay put” flexible spigot that directs and holds power rinse where you want it.

For use with petroleum based solvents with a flash point over 104°F. Not to be used with chlorinated solvents.

### Features

- » Durable baked on powder coated epoxy finish
- » Meets 0.75 freeboard requirements
- » Easy assembly with four bolts
- » Heavy-duty pump
- » Removable screen filter for pump protection
- » Fire-protected lid closure 165°F
- » Stay-put flexible metal spigot
- » On/Off switch conveniently located on side of washer

### Specifications

- » Overall dimensions: 34" L x 19" W x 56" H
- » Inside dimensions: 31" L x 18" W x 8¼" H
- » Shipping dimensions: 34" L x 20½" W x 12½" H
- » Weight: 45 lbs.
- » Fluid capacity: 30 gallon (drum optional)
- » Maximum fluid depth: 26½"
- » Minimum fluid depth: 13"
- » Load lift over: 37"
- » Voltage: 115VAC/60HZ/1PH/1 Amp
- » Pump: Fractional

### Accessories

- » 54527 10 Micron filter kit
- » 59173 50 Micron filter kit
- » 54961 Bolt-on light
- » K7322 30 gallon drum
- » RA39 Drum liner





## SOLVENT PARTS WASHER

### CleanMaster 116

» Economy drum mounted solvent parts washer. Built-to-last for years of reliable service. Equipped with “stay put” flexible spigot that directs and holds power rinse where you want it.

For use with petroleum based solvents with a flash point over 104°F. Not to be used with chlorinated solvents.

### Features

- Durable baked on powder coated epoxy finish
- Meets 0.75 freeboard requirements
- Easy assembly with four bolts
- Heavy-duty pump
- Removable screen filter for pump protection
- Fire-protected lid closure 165°F
- Stay-put flexible metal spigot
- On/Off switch conveniently located on side of washer

### Specifications

- Overall dimensions: 30" L x 18" W x 43" H
- Inside dimensions: 27" L x 16" W x 8" H
- Shipping dimensions: 30½" L x 18½" W x 11½" H
- Weight: 39 lbs.
- Fluid capacity: 16 gallon (drum optional)
- Maximum fluid depth: 24"
- Minimum fluid depth: 11¾"
- Load lift over: 35¼"
- Voltage: 115VAC/60HZ/1PH/1 Amp
- Pump: Fractional

### Accessories

- 54527 10 Micron filter kit
- 59173 50 Micron filter kit
- 54961 Bolt-on light
- K7197 16 gallon drum
- RA39 Drum liner



# SOLVENT PARTS WASHER

## CleanMaster 230

Industrial drum mounted solvent parts washer. Built-to-last for years of reliable service. Equipped with flow-through brush and “stay-put” flexible spigot that directs and holds power rinse where you want it.

For use with petroleum based solvents with a flash point over 104°F.  
Not to be used with chlorinated solvents.

### Features

- Removable screen filter for pump protection
- Stay-put flexible metal spigot
- Flow-through brush with adjustable fluid control
- Durable baked on powder coated epoxy finish
- Meets 0.75 freeboard requirements
- Heavy-duty industrial grade pump
- Spring loaded door closure with fusible link 165°F
- Single on/off switch for pump and optional light kit
- Galvanized drawn sink

### Specifications

- Overall dimensions: 34½" L x 26½" W x 63" H
- Inside dimensions: 32" L x 24" W x 7 ½" H
- Shipping dimensions: 37" L x 28" W x 16" H
- Weight: 68 lbs.
- Fluid capacity: 30 gallon (drum optional)
- Maximum fluid depth: 26½"
- Minimum fluid depth: 8¼"
- Load lift over: 37
- Voltage: 115VAC/60HZ/1PH/1 Amp
- Pump: Fractional

### Accessories

- 54527 10 Micron filter kit
- 59173 50 Micron filter kit
- 54961 Bolt-on light
- K7322 30 gallon drum
- RA39 Drum liner





## SOLVENT PARTS WASHER

### CleanMaster 216

» Industrial drum mounted solvent parts washer. Built-to-last for years of reliable service. Equipped with flow-through brush and “stay-put” flexible spigot that directs and holds power rinse where you want it. For use with petroleum based solvents with a flash point over 104°F. Not to be used with chlorinated solvents.

### Features

- » Removable screen filter for pump protection
- » Stay-put flexible metal spigot
- » Flow-through brush with adjustable fluid control
- » Durable baked on powder coated epoxy finish
- » Meets 0.75 freeboard requirements
- » Heavy-duty industrial grade pump
- » Spring loaded door closure with fusible link 165°F
- » Single on/off switch for pump and optional light kit
- » Galvanized drawn sink



### Specifications

- » Overall dimensions: 31" L x 21" W x 56" H
- » Inside dimensions: 28" L x 18" W x 7½" H
- » Shipping dimensions: 32½" L x 22½" W x 15½" H
- » Weight: 54 lbs.
- » Fluid capacity: 16 gallon (drum optional)
- » Maximum fluid depth: 24"
- » Minimum fluid depth: 8"
- » Load lift over: 36½"
- » Voltage: 115VAC/60HZ/1PH/1 Amp
- » Pump: Fractional

### Accessories

- » 54527 10 Micron filter kit
- » 59173 50 Micron filter kit
- » 54961 Bolt-on light
- » K7197 16 gallon drum
- » RA39 Drum liner





# SOLVENT PARTS WASHER

## CleanMaster 200

Clean and Soak solvent parts washer. Equipped with “stay-put” flexible spigot that directs and holds power rinse where you want it. For use with petroleum based solvents with a flash point over 104°F. Not to be used with chlorinated solvents.

### Features

- » Durable, baked on powder coated epoxy finish
- » Removable inside cabinet shelf
- » Spring loaded door closure with fusible link 165°F
- » Screened sludge filter pad
- » Built-in drain with plug
- » Heavy-duty metal stand and shelf
- » Stay-put flexible metal spigot



### Specifications

- » Overall dimensions: 35<sup>3</sup>/<sub>4</sub>" L x 23<sup>3</sup>/<sub>4</sub>" W x 60" H
- » Inside dimensions: 34<sup>1</sup>/<sub>2</sub>" L x 23<sup>1</sup>/<sub>2</sub>" W x 16<sup>3</sup>/<sub>4</sub>" D
- » Shipping dimensions: 40" L x 26" W x 23" H
- » Weight: 133 lbs.
- » Fluid capacity: 30 gallon
- » Maximum fluid depth: 8<sup>1</sup>/<sub>2</sub>"
- » Minimum fluid depth: 5<sup>1</sup>/<sub>4</sub>"
- » Load lift over: 35
- » Soaking depth: 8<sup>1</sup>/<sub>2</sub>"
- » Voltage: 115VAC/60HZ/1PH/1 Amp
- » Pump: Fractional

### Accessories

- » 54527 10 Micron filter kit
- » 59173 50 Micron filter kit
- » 02923 Heavy-duty light kit
- » 54961 Bolt-to-Lid light kit
- » K7945 Flo-thru hose and brush
- » 50542-3 Parts basket







## SOLVENT PARTS WASHER

### CleanMaster 440

Clean and Soak solvent parts washer. Equipped with pistol grip spray nozzle and "stay-put" flexible spigot that directs and holds power rinse where you want it. For use with petroleum based solvents with a flash point over 104°F.

Not to be used with chlorinated solvents.

### Features

- Durable, baked on powder coated epoxy finish
- Spring loaded door closure with fusible link 165°F
- ¾" drain plug located on bottom front of the machine
- easy draining
- Stay-put flexible metal spigot
- Pistol grip spray nozzle
- Removable inside cabinet shelf



### Specifications

- Overall dimensions: 44" L x 24¼" W x 61" H
- Inside dimensions: 43" L x 24" W x 17" D
- Shipping dimensions: 48" L x 27½" W x 20½"
- Weight: 175 lbs.
- Fluid Capacity: 40 gallon
- Maximum fluid depth: 8¾"
- Minimum fluid depth: 5¼"
- Load lift over: 36"
- Soaking depth: 9"
- Voltage: 115V/60HZ/1PH/1 Amp
- Pump: Fractional

### Accessories

- 54527 10 Micron filter kit
- 59173 50 Micron filter kit
- 02923 Heavy-duty light kit
- 54961 Bolt-to-lid light kit
- K7945 Flo-thru hose and brush
- 50023-3 Parts tray





## SOLVENT PARTS WASHER

### CleanMaster 80

Agitating lift solvent parts washer. Equipped with flow through brush. Heavy-duty automated lift platform rises out of the solvent for easy loading and unloading of parts. For use with petroleum based solvents with a flash point over 104°F.

Not to be used with chlorinated solvents.

### Features

- Pre-set 120 psi filter regulator with auto drain
- Lift operates on 120 psi air pressure
- Flow-through hand held brush
- 12-gauge tank thickness
- Agitation speed adjustable from 0 to 160 agitations per minute

### Specifications

- Overall dimensions: 52½" L x 34" W x 66½" H
- Inside dimensions: 44½" L x 27¼" W x 28" D
- Carrier dimensions: 41½" L x 17½" W
- Shipping dimensions: 56½" L x 36½" W x 56" H
- Shipping weight: 556 lbs.
- Fluid capacity: 80 gallons
- Maximum fluid depth: 15¼"
- Minimum fluid depth: 9¼"
- Load lift over: 38"
- Load capacity: 250 lbs.
- Lift requirements: 8CFM@120 PSI
- Voltage: 115V/60HZ/1PH/1 Amp
- Pump: Fractional

### Accessories

- 61647 50 Micron filter kit
- 54961 Bolt-on light kit
- 02923 Industrial light kit





## SOLVENT PARTS WASHER

### CleanMaster 150

Agitating lift solvent parts washer. Equipped with flow through brush. Heavy duty automated lift platform rises out of the solvent for easy loading and unloading of parts. For use with petroleum based solvents with a flash point over 104°F.

Not to be used with chlorinated solvents.

### Features

- Pre-set 120 psi filter regulator with auto drain
- Lift operates on 120 psi air pressure
- Flow-through hand held brush
- 10-gauge tank thickness
- Agitation speed adjustable from 0 to 160 agitations per minute

### Specifications

- Overall dimensions: 64" L x 44½" W x 69½" H
- Inside dimensions: 57" L x 37¾" W x 29 D
- Carrier dimensions: 53½" L x 27½" W
- Shipping dimensions: 66" L x 48" W x 51" H
- Shipping weight: 750 lbs.
- Fluid capacity: 150 gallons
- Maximum fluid depth: 17¼"
- Minimum fluid depth: 9¼"
- Load lift over: 41"
- Load capacity: 750 lbs.
- Lift requirements: 25CFM@120 PSI
- Voltage: 115V/60HZ/1PH/1 Amp
- Pump: Fractional

### Accessories

- 61647 50 Micron filter kit
- 54961 Bolt-on light kit
- 02923 Industrial light kit





## SOLVENT PARTS WASHER

### CleanMaster IC

Air Operated Agitating Drum Washer. Air-powered unit for use with parts degreaser or carburetor cleaner. Heavy-duty airopowered motor that

#### Features

- » Rugged metal basket
- » Basket hookup for easy installation
- » Lever-lock band for sealing cover
- » Operates with 20 psi or more air pressure

#### Specifications

- » Overall dimensions: 16" W x 31" H
- » Basket dimensions: 11½" DIA x 7½" D
- » Shipping dimensions: 19" L x 16½" W x 24" H
- » Weight: 50 lbs.
- » Fluid capacity: 16 gallon (drum optional)
- » Maximum fluid depth: 24"
- » Minimum fluid depth: 10"
- » Fits 16 gallon drum

#### Accessories

- » K7197 Optional drum





## SOLVENT PARTS WASHER

### CleanMaster 250 / 500

An environmentally sound choice, an economical investment, and a profit making business all-in-one machine. Our Anti- Freeze Recyclers turn disposal problems into increased profits for fleet operations, dealer service centers, and other automotive maintenance operations. With the Anti-Freeze Recycler system, you remove harmful particulates and restore anti-corrosion additives. No hot vapors or heating and cooling cycles. You can reuse anti-freeze with the performance of new.

### Features

- Lowest cost-per-gallon of recycled coolant
- Passed stringent testing and earned General Motors approval for DEX-COOL® mixtures
- Saves the environment, money and creates profit
- Easiest anti-freeze recyclers to operate; no hoses to cut, easy filter changes, no special wiring required
- Fill through Strainer Filter Bag
- Anti-Freeze drained from vehicles is poured easily into the 25 gallon "Dirty" tank through bag type filter in top of machine
- Comfortable loading height
- Stainless steel construction
- Patented Model AF250
- Cleaned anti-freeze is recycled into an optional PL drum where it may be dispensed through optional R10 Roto-Pump when needed
- Easy access to filters and gauges
- Recycled coolant meets GM and ASTM standards when using the AF250 and Preparal®

### Specifications

- Overall dimensions CM250: 35" L x 22½" W x 39" H
- Overall dimensions CM500: 35" L x 34" W x 39" H
- Inside dimensions CM250: 23¾" L x 11¾" W x 26" H
- Inside dimensions CM500: 23¾" L x 23¾" W x 26" H
- Shipping dimensions CM250: 40" L x 48" W x 43" H
- Shipping dimensions CM500: 40" L x 48" W x 43" H
- Tank capacity: CM250 – 25 gallon
- Tank capacity: CM500 – 50 gallon
- Voltage: 115V/1PH Amp
- Weight: CM250 – 245 lbs., CM500 – 275 lbs.
- Gallons cleaned per hour: 5

### Operation as Easy as One-Two-Three!



1. Simply pour used coolant through the strainer bag into the "Dirty" tank. After you reach the fill level, place the output hose into an empty, clean drum.
2. To begin the recycling process, hit start and walk away. The recycling begins through the ultra filtration process and shuts itself off automatically.
3. Then, simply add Preparal® to the recycled batch to restore the proper balance of additives to maintain the anti-corrosion properties of the coolant. Check the freeze point and adjust if necessary. The recycled coolant meets GM and ASTM standards.



### Accessories

- 193527 Main filter
- 193576 Cartridge filters
- 193573 Additive inhibitor (gasoline)
- 193574 Additive inhibitor (diesel)
- 02-11831 PL drum
- 02-11834 Roto-pump



## AQUEOUS PARTS WASHERS

### EcoMaster 50

» Table top aqueous parts washer. Equipped with flow-through brush which works great for cleaning small parts. For use with an aqueous based cleaning solution.

#### Features

- Corrosion resistant heavy-duty pump
- Flo-through brush
- Heavy-duty, high density polyethylene fluid tank
- Stainless steel lid and top

#### Specifications

- Tank dimensions: 19½" L x 14" W x 7½" D
- Overall dimensions: 22" L x 16" W x 24" H
- Shipping dimensions: 23½" L x 18" W x 11½" H
- Weight: 20 lbs.
- Fluid Capacity: 5 gallons
- Maximum fluid depth: 5"
- Minimum fluid depth: 2¾"
- 115V/60HZ/1PH/1 Amp
- Pump: Fractional





## AQUEOUS PARTS WASHERS

### EcoMaster 50H

Heated table top aqueous parts washer. Equipped with flow through brush which works great for cleaning small parts.

For use with an aqueous based cleaning solution.

### Features

- Corrosion resistant heavy-duty pump
- Flo-through brush
- Heavy-duty, high density polyethylene fluid tank
- Stainless steel lid and top
- Heated unit

### Specifications

- Tank dimensions: 19½" L x 14" W x 7½" D
- Overall dimensions: 22" L x 16" W x 24" H
- Shipping dimensions: 23½" L x 18" W x 11½" H
- Weight: 20 lbs.
- Fluid capacity: 5 gallons
- Maximum fluid depth: 5"
- Minimum fluid depth: 2¾"
- 115V/60HZ/1PH/5 Amp
- Pump: Fractional
- Heater: 500 W







## AQUEOUS PARTS WASHERS

### EcoMaster 1435

Aqueous portable brake washer. Drum mounted for easy waste disposal. Our dual filtration system helps to extend the life of the cleaning solution. Equipped with a flow through brush and spigot; making your cleaning job fast and easy. The dual purpose cover can be used as a cover or as a catch basin.

Use it on alignment lifts, ramp lifts or place it on the floor. For use with an aqueous based cleaning solution.

### Features

- Heavy-duty air pump
- Convenient flexible metal spigot for those tough cleaning jobs
- Features “on-off” valve
- Heavy-duty drum dolly with two locking casters and two regular casters
- 15 gallon heavy-duty drum
- Adjustable pressure regulator
- Dual filtration system
- Prefilter screen and asbestos sock filter designed to insure clean solution
- Designed for easy servicing, remove basin from drum in minutes
- Can be used as a portable parts washer or brake washer
- Also available with heat

### Specifications

- Sink dimensions: 24” L x 20” W x 7” D
- Overall dimensions: 28” L x 28” W x 41” H
- Shipping dimensions: 30” L x 25” W x 35” H
- Weight: 72 lbs.
- Fluid capacity: 12 gallons
- Maximum fluid depth: 15¾”
- Minimum fluid depth: 6½”
- Load lift over: 41”





## AQUEOUS PARTS WASHERS

### EcoMaster 235

» Drum mounted aqueous parts washer. Equipped with a flow through brush and spigot; making your cleaning job fast and easy.

Designed for easy removal of old solution by swapping out the drum. For use with an aqueous based cleaning solution.

### Features

- Industrial-grade pump
- Stainless steel work shelf included
- Fixed thermostat is preset to deliver optimal cleaning temperature of 110°F
- Includes non-adjustable backup thermostat
- Separate heater and pump switches with on/off indicators
- Ground fault circuit interrupter for added shock resistant safety
- Flow-through brush and spigot with adjustable fluid control
- Spring loaded door closure with fusible link 165°F



### Specifications

- Overall dimensions: 36¼" L x 31½" W x 63" H
- Inside dimensions: 34" L x 22" W x 9" D
- Shipping dimensions: 36½" L x 29" W x 17" H
- Weight: 87 lbs.
- Fluid capacity: 30 gallon (drum optional)
- Maximum fluid depth: 25"
- Minimum fluid depth: 12"
- Soaking depth: 8"
- Load Lift Over: 41"
- Voltage: 115V/60HZ/1PH/10 Amps
- Pump: Fractional
- Heater: 1000 W

### Accessories

- » 56452 Filter kit
- » 54961 Light kit
- » 8927 Optional polyethylene drum





## AQUEOUS PARTS WASHERS

### EcoMaster 230S

Stainless steel drum mounted aqueous parts washer. Equipped with a flow-through brush and spigot; making your cleaning job fast and easy. Designed for easy removal of old solution by swapping out the drum. For use with an aqueous based cleaning solution.

### Features

- Ground fault circuit interrupter for added shock resistant safety
- Heater thermostatically controlled pre- set to 110°F
- Thermostat capillary protected by stainless steel thermo well, chemical resistant
- Dual switches – heater and pump
- Stainless steel drain filter system
- Flow-through brush and spigot with adjustable fluid control
- Spring-loaded door closure with fusible link 165°F

### Specifications

- Overall dimensions: 35¾" L x 28¾" W x 61½" H
- Inside dimensions: 32" L x 24" W x 7¼" D
- Shipping dimensions: 36½" L x 30½" W x 15½" H
- Weight: 80 lbs.
- Fluid capacity: 30 gallon (drum optional)
- Maximum fluid depth: 25"
- Minimum fluid depth: 13"
- Load lift over: 36½"
- Voltage: 115V/60HZ/1PH/15 Amps
- Pump: Fractional
- Heater: 1000 W

### Accessories

- 8927 Optional polyethylene drum
- 54961 Light kit





## AQUEOUS PARTS WASHERS

### EcoMaster 1350H

» Stainless steel drum mounted aqueous parts washer. Equipped with a flow-through brush and spigot; making your cleaning job fast and easy. Designed for easy removal of old solution by swapping out the drum. For use with an aqueous based cleaning solution.

### Features

- » Ground fault circuit interrupter for added shock resistant safety
- » Heater thermostatically controlled preset to 110°F
- » Thermostat capillary protected by stainless steel thermo well, chemical resistant
- » Dual switches – heater and pump
- » Heated unit 115 volts, 15 amps
- » Stainless steel drain filter system
- » Flow-through brush and spigot with adjustable fluid control
- » Spring-loaded door closure with fusible link 165°F

### Specifications

- » Overall dimensions: 35" L x 28" W x 60½" H
- » Inside dimensions: 32" L x 22" W x 8" D
- » Shipping dimensions: 36½" L x 31" W x 15½" H
- » Weight: 80 lbs.
- » Fluid capacity: 30 gallon (drum optional)
- » Maximum fluid depth: 25"
- » Minimum fluid depth: 14"
- » Load lift over: 37"
- » Voltage: 115V/60HZ/1PH/15 Amps
- » Pump: Fractional
- » Heater: 1000 W

### Accessories

- » 8927 Optional Polyethylene Drum
- » 54961 Light kit





## AQUEOUS PARTS WASHERS

### EcoMaster 6000

» Clean or soak aqueous parts washer. Equipped with a dual filter system, flow through brush and spigot; making your cleaning job fast and easy. This unit could be used as a stationary parts washer or use with the optional rolling cart for a more portable solution. For use with an aqueous based cleaning solution.

### Features

- » Corrosion resistant heavy-duty pump
- » Ground fault circuit interrupter for added safety
- » Heater thermostatically controlled preset to 110°F
- » Flow-through brush and spigot with adjustable fluid control
- » Thermowell for protection of the thermostat capillary bulb
- » Stainless steel lid and lid closure
- » Quick sink removable for easy servicing
- » Filter system prolongs fluid life
- » Low-level fluid sensor
- » Heavy-duty door closure with fusible link 165°F

### Specifications

- » Overall dimensions: 34" L x 23" W x 33" H
- » Sink dimensions: 34" L x 23" W x 9" D
- » Shipping dimensions: 40" L x 30" W x 35" H
- » Weight: 80 lbs.
- » Fluid capacity: 40 gallons
- » Maximum fluid depth: 14¾"
- » Minimum fluid depth: 8"
- » Load lift over: 34"
- » Soaking capacity: 10 gallons
- » Capacity: 45 gallons
- » Voltage: 115V/60HZ/1PH/15 Amp
- » Pump: Fractional
- » Heater: 1000 W

### Accessories

- » 61332 Cart
- Shipping dimensions: 39" L x 31" W x 10½" H
- » 193445 Light kit





## AQUEOUS PARTS WASHERS

### EcoMaster 5000

» Reservoir mounted aqueous parts washer. Designed for easy servicing – sink can be removed from reservoir in seconds.

Equipped with a dual filter system, flow-through brush and spigot; making your cleaning job fast and easy. For use with an aqueous based cleaning solution.

### Features

- » Corrosion resistant heavy-duty pump
- » Flo-through brush and spigot with adjustable fluid control
- » Reservoir engineered to provide excellent tank stability
- » Filter system prolongs fluid life. Filter cartridge P/N 7062
- » Automatic thermostat preset to 110°F
- » Ground fault circuit interrupter for added safety
- » Dual switches: heater and pump
- » Low-level fluid sensor
- » Heavy-duty door closure with fusible link 165°F

### Specifications

- » Sink dimensions: 36" L x 22½" W x 9" D
- » Overall dimensions: 42" L x 35" W x 65" H
- » Shipping dimensions: 41" L x 34" W x 39" H
- » Weight: 170 lbs.
- » Fluid capacity: 30 gallons
- » Maximum fluid depth: 16"
- » Minimum fluid depth: 8½"
- » Load lift over: 38"
- » Voltage: 115V/60HZ/1PH/15 Amp
- » Pump: Fractional
- » Heater: 1000 W

### Accessories

- » 193445 Light kit
- » 193589-02 Soak tray







## AQUEOUS PARTS WASHERS

### EcoMaster 4000

» Clean and soak aqueous parts washer. Equipped with a filter system, flow-through brush, spigot, and mechanical fluid agitation; making your cleaning job fast and easy. For use with an aqueous based cleaning solution.

### Features

- » Corrosion resistant heavy-duty pump
- » Dual switches: heater and pump
- » Ground fault circuit interrupter for added shock resistant safety
- » Filter system – prolongs fluid life Filter cartridge PN K8419
- » Heater thermostatically controlled- preset to 110°F
- » Mechanical agitation – 15 spray heads with fluid control valve
- » Flow-thru brush and spigot with adjustable fluid control
- » Heavy-duty door closure with fusible link 165°F

### Specifications

- » Sink dimensions: 36" L x 26" W x 18" D
- » Overall dimensions: 45" L x 29" W x 66" H
- » Shipping dimensions: 46½" L x 35½" W x 41" H
- » Weight: 155 lbs.
- » Soaking capacity: 30 gallons
- » Fluid capacity: 30 gallons
- » Maximum fluid depth: 7½"
- » Minimum fluid depth: 4"
- » Load lift over: 38½"
- » Voltage: 115V/60HZ/1PH/12 Amp
- » Pump: Fractional
- » Heater: 1000 W

### Accessories

- » 193445 Light kit







## AQUEOUS PARTS WASHERS

### EcoMaster 40

» Agitating lift aqueous parts washer. Featuring Fountain Industries patented lift system! Heavy duty automated lift platform rises out of the solution for easy loading and unloading of parts. Equipped with flow through brush. For use with an aqueous based cleaning solution.

### Features

- » Thermostat is pre-set to 130°F
- » Adjustable agitation speed
- » Filter regulator with auto drain
- » Not to be used with chlorinated solvents
- » Flow-through brush

### Specifications

- » Overall dimensions: 27" W x 34½" L x 59" H
- » Inside dimensions: 29¾" L x 24" L x 24" H
- » Shipping dimensions: 37¾" L x 29½" W x 45" H
- » Carrier dimensions: 24" L x 18" W
- » Shipping weight: 225 lbs.
- » Fluid capacity: 50 gallons
- » Maximum fluid depth: 16"
- » Minimum fluid depth: 4"
- » Load lift over: 32"
- » Load capacity: 100 lbs.
- » Lift requirements: 20CFM@40 PSI
- » Pump voltage: 115V/60HZ/1PH/1 Amp
- » Pump motor HP: Fractional
- » Heater voltage: 230V/60HZ/1PH /12 Amp
- » Heater: 2500 W
- » Tank thickness: 12 gauge

### Accessories

- » 61647 50 Micron filter kit





## AQUEOUS PARTS WASHERS

### EcoMaster 80

» Agitating lift aqueous parts washer. Heavy-duty automated lift platform rises out of the solution for easy loading and unloading of parts. Equipped with flow through brush. For use with an aqueous based cleaning solution.

### Features

- » Thermostat is pre-set to 110°F
- » Adjustable agitation speed
- » Stainless steel spring-loaded door closure with fusible link 165°F
- » Filter regulator with auto drain
- » Includes backup thermostat (non-adjustable)
- » Not to be used with chlorinated solvents
- » Flow-through brush

### Specifications

- » Overall dimensions: 52½" L x 34" W x 66½" H
- » Inside dimensions: 44½" L x 27¼" W x 28" D
- » Shipping dimensions: 56½" L x 36½" W x 56" H
- » Carrier dimensions: 42½" L x 17½" W
- » Shipping weight: 556 lbs.
- » Fluid capacity: 80 gallons
- » Maximum fluid depth: 15¼"
- » Minimum fluid depth: 9¼"
- » Load lift over: 38"
- » Load capacity: 250 lbs.
- » Lift requirements: 8CFM@120 PSI
- » Pump voltage: 115V/60HZ/1PH/1 Amp
- » Heater voltage: 230V/60HZ/1PH/30 Amp
- » Heater watts: 3000 W

### Accessories

- » 61647 50 Micron filter kit
- » 02923 Industrial light kit
- » 054961 Bolt-on light





## AQUEOUS PARTS WASHERS

### EcoMaster 150

» Agitating lift aqueous parts washer. Heavy duty automated lift platform rises out of the solution for easy loading and unloading of parts. Equipped with flow through brush. For use with an aqueous based cleaning solution.

### Features

- » Thermostat is pre-set to 110°F
- » Adjustable agitation speed
- » Stainless steel spring-loaded door closure with fusible link 165°F
- » Filter regulator with auto drain
- » Includes backup thermostat (non-adjustable)
- » Not to be used with chlorinated solvents
- » Flow-through brush

### Specifications

- » Overall dimensions: 64" L x 44½" W x 69½" H
- » Inside dimensions: 57" L x 37¾" W x 30" D
- » Shipping dimensions: 66" L x 48" W x 51" H
- » Carrier dimensions: 53½" L x 27½" W
- » Shipping weight: 1,115 lbs
- » Fluid capacity: 163 gallons
- » Maximum fluid depth: 17½"
- » Minimum fluid depth: 9¼"
- » Load lift over: 37½"
- » Load capacity: 750 lbs.
- » Lift requirements: 25CFM@120 PSI
- » Pump voltage: 115V/60HZ/1PH/1 Amp
- » Heater voltage: 230V/60HZ/1PH/30 Amp
- » Heater watts: 3000 W

### Accessories

- » 61647 50 Micron filter kit
- » 02923 Industrial light kit
- » 54961 Bolt-on light





## AQUEOUS PARTS WASHERS

### SprayMaster 9200

» Top load automatic spray cabinet washer. Requires no more floor space than the standard drum mounted parts washer.

Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. For use with an aqueous based cleaning solution.

### Features

- » 24" turntable
- » 23" inside working height
- » Adjustable cycle timer from 0 to 60 minutes
- » Stainless steel gasket-free lid for maintenance free operation
- » Friction turntable drive
- » Liquid level sensor
- » Movable top arm for easy loading and unloading

### Specifications

- » Overall dimensions: 34" L x 36" W x 50" H
- » Inside dimensions: 24" L x 24" W x 23" H
- » Shipping dimensions: 40" L x 48" W x 76" H
- » Shipping weight: 416 lbs.
- » Fluid capacity: 32 gallons
- » Maximum fluid depth: 10"
- » Minimum fluid depth: 6½"
- » Load lift over: 34"
- » Turntable dimensions: 24"
- » Load capacity: 250 lbs.
- » Voltage: 230V/60HZ/1PH Amp
- » Amps: 30
- » Pump HP: ¾
- » Heater: 4.5 KW





## AQUEOUS PARTS WASHERS

### SprayMaster 9200SS

» Stainless steel top load automatic spray cabinet washer. Requires no more floor space than the standard drum mounted parts washer. Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. Equipped with fluid level shut off to protect the heater elements. For use with an aqueous based cleaning solution.

#### Features

- » 24" turntable
- » 23" inside working height
- » Adjustable cycle timer from 0 to 60 minutes
- » Stainless steel gasket-free lid for maintenance free operation
- » Friction turntable drive
- » Liquid level sensor
- » Movable top arm for easy loading and unloading

#### Specifications

- » Overall dimensions: 34" L x 36" W x 50" H
- » Inside dimensions: 24" L x 24" W x 23" H
- » Shipping dimensions: 40" W x 48" L x 76" H
- » Shipping weight: 416 lbs.
- » Fluid capacity: 32 gallons
- » Maximum fluid depth: 10"
- » Minimum fluid depth: 6½"
- » Load lift over: 34"
- » Turntable dimensions: 24"
- » Load capacity: 250 lbs.
- » Voltage: 230V/60HZ/1PH Amp
- » Amps: 30
- » Pump HP: ¾
- » Heater: 4.5 KW





## AQUEOUS PARTS WASHERS

### SprayMaster 9400

» Economy front load automatic spray cabinet washer. Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. Equipped with automatic oil skimmer and fluid level shut off to protect the heater elements. For use with an aqueous based cleaning solution.

#### Features

- » 40" inside working height
- » 30" turntable
- » 60 gallon fluid capacity
- » 12" stainless steel disc skimmer with 45 minute timer
- » Friction turntable drive will not break if a part becomes lodged
- » Removable tree rack standard
- » Portable with (4) casters
- » Adjustable cycle timer from 0 to 60 minutes

#### Specifications

- » Overall dimensions: 42" L x 50" W x 65" H
- » Inside dimensions: 30" L x 30" W x 40" H
- » Shipping dimensions: 50½" L x 59" W x 76"
- » Shipping weight: 937 lbs.
- » Fluid capacity: 60 gallons
- » Maximum fluid depth: 10"
- » Minimum fluid depth: 7"
- » Load lift over: 23¼"
- » Turntable dimensions: 30"
- » Load capacity: 500 lbs.
- » Voltage: 230V/60HZ//1PH
- » Amps: 45
- » Pump HP: 1.5
- » Heater: 6.0 KW







## AQUEOUS PARTS WASHERS

### SprayMaster 9600

» Front load automatic spray cabinet washer. Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. Equipped with automatic oil skimmer and fluid level shut off to protect the heater elements. For use with an aqueous based cleaning solution.

#### Features

- » 40" inside working height
- » 30" turntable
- » 70 gallon fluid capacity
- » Adjustable heat timer allows you to keep solution hot overnight
- » Adjustment cycle timer from 0 to 60 minutes
- » 12" stainless steel disc skimmer with 45 minute timer
- » Center spray bar folds down for cleaning of smaller parts
- » Friction turntable drive will not break if a part becomes lodged
- » Removable tree rack standard
- » Stainless steel nozzles
- » Portable with (4) casters

#### Specifications

- » Overall dimensions: 42" L x 50" W x 65" H
- » Inside dimensions: 30" L x 30" W x 40" H
- » Shipping dimensions: 50½" L x 59" W x 76" H
- » Shipping weight: 1,070 lbs.
- » Fluid capacity: 70 gallons
- » Maximum fluid depth: 9¾"
- » Minimum fluid depth: 7"
- » Load lift over: 23¼"
- » Turntable dimensions: 30"
- » Load capacity: 500 lbs.
- » Voltage: 230V/60HZ//1PH Amp
- » Amps: 60
- » Pump HP: 3
- » Heater: 9.0 KW







## AQUEOUS PARTS WASHERS

### SprayMaster 9600SS

» Stainless Steel front load automatic spray cabinet washer. Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. Equipped with automatic oil skimmer and fluid level shut off to protect the heater elements. For use with an aqueous based cleaning solution.

#### Features

- » 40" inside working height
- » 30" turntable
- » 70 gallon fluid capacity
- » Adjustable heat timer allows you to keep solution hot overnight
- » Adjustment cycle timer from 0 to 60 minutes
- » 12" stainless steel disc skimmer with 45 minute timer
- » Center spray bar folds down for cleaning of smaller parts
- » Friction turntable drive will not break if a part becomes lodged
- » Removable tree rack standard
- » Stainless steel nozzles
- » Portable with (4) casters

#### Specifications

- » Overall dimensions: 42" L x 50" W x 68" H
- » Inside dimensions: 30" L x 30" W x 40" H
- » Shipping dimensions: 50½" L x 59" W x 76" H
- » Shipping weight: 1,070 lbs.
- » Fluid capacity: 70 gallons
- » Maximum fluid depth: 9¾"
- » Minimum fluid depth: 7"
- » Load lift over: 23¼"
- » Turntable dimensions: 30"
- » Load capacity: 500 lbs.
- » Voltage: 230V/60HZ//1PH
- » Amps: 60
- » Pump HP: 3
- » Heater: 9.0 KW





## AQUEOUS PARTS WASHERS

### SprayMaster 9800SS

» Stainless Steel front load automatic spray cabinet washer. Parts rotate on an automated turntable to get complete 360 degree coverage for effective cleaning of parts. Equipped with automatic oil skimmer and fluid level shut off to protect the heater elements. For use with an aqueous based cleaning solution.

### Features

- » 12" Skimmer with 45 minute timer
- » Liquid level sensor automatically turns off heaters before they burn out
- » 22 stainless steel nozzles
- » Adjustable heat timer allows you to keep solution hot over night
- » Adjustable cycle timer from 0 to 60 minutes
- » Center spray bar folds down for smaller parts
- » Removable parts tree
- » Stainless steel construction

### Specifications

- » Overall dimensions: 54½" L x 60" W x 77" H
- » Inside dimensions: 40" L x 40" W x 52" H
- » Shipping dimensions: 68" L x 75" W x 90" H
- » Shipping weight: 1,550 lbs.
- » Fluid capacity: 135 gallons
- » Maximum fluid depth: 12"
- » Minimum fluid depth: 10"
- » Load lift over: 24"
- » Load capacity: 1,250 lbs.
- » Inside working height: 52"
- » Turntable dimensions: 40"
- » Pump rating: 5.0 HP 140GPM at 50 PSI
- » Voltage: 230V/60HZ/3PH
- » Amps: 60
- » Heater watts: 13,500 W

